

RICH-COTE FORM RELEASE SUMMER GRADE

TECHNICAL DATA SHEET

BASIC DESCRIPTION

RICH-COTE FORM RELEASE SUMMER GRADE is a blend of natural and synthetic chemicals that uses a chemical reaction to provide quick, easy and clean release of concrete from forms.

USES

RICH-COTE FORM RELEASE SUMMER GRADE is used on metal, wood, plastic and fiberglass forms; also on pans and tubes for roof and column work.

CHARACTERISTICS

RICH-COTE FORM RELEASE SUMMER GRADE acts as a bond breaker and form cleaner; is non-staining, will not wash off; cuts cleanup time; eliminates voids, defects and buildup of concrete and mortar; protects forms from rusting; and is economical and easy to use.

PACKAGING

18.9 Litre Pails
205 Litre Drums

COVERAGE

14.7 - 40.9 m²/L (719 - 2000 ft.²/gal.). Coverage rate will vary depending on the method of application and the type of form. Recommended application rates are approximate.

STANDARDS

Complies with Canada VOC Concentration Limits for Architectural Coatings Regulations.

INSTALLATION INSTRUCTIONS

Apply by low-pressure sprayer, such as a Chapin 1949 with a 0.379 LPM nozzle, in a light, even coat. When employing a brush or roller, take care to apply as thinly and evenly as possible. A thin coating provides superior results. New wood forms (not pre-coated) should receive at least two coats before being used. All forms should be recoated before each subsequent use.

BEST USED BY

When stored indoors in original, unopened containers at temperatures between 4° - 32° C, optimum performance and best use is obtained within two years of date of manufacture.

PRECAUTIONS

For exterior use only. For industrial use only.
To be used at temperatures above 3° C (37° F).

WARRANTY

National Concrete Accessories warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after National Concrete Accessories has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. National Concrete Accessories shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by National Concrete Accessories. We cannot warrant or in any way guarantee any particular method of use or application of the performance of materials under and particular condition. Neither this Warranty nor our liability may be extended or amended by our sales personnel, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.

WARNING

The information contained on this package and in any promotional literature is believed to be accurate but the user assumes all risks connected with the use thereof and should conduct its own investigations and perform its own tests to determine the suitability of the product for its own particular use. Use in unsuitable circumstances can cause serious damages for which NCA is not responsible.

RICH-COTE FORM RELEASE WINTER GRADE

TECHNICAL DATA SHEET

BASIC DESCRIPTION

RICH-COTE FORM RELEASE WINTER GRADE is a blend of natural and synthetic chemicals that uses a chemical reaction to provide quick, easy and clean release of concrete from forms.

USES

RICH-COTE FORM RELEASE WINTER GRADE is used on metal, wood, plastic and fiberglass forms; also on pans and tubes for roof and column work.

CHARACTERISTICS

RICH-COTE FORM RELEASE WINTER GRADE acts as a bond breaker and form cleaner; is non-staining, will not wash off; cuts cleanup time; eliminates voids, defects and buildup of concrete and mortar; protects forms from rusting; and is economical and easy to use.

PACKAGING

18.9 Litre Pails
205 Litre Drums

COVERAGE

14.7 - 40.9 m²/L (719 - 2000 ft.²/gal.). Coverage rate will vary depending on the method of application and the type of form. Recommended application rates are approximate.

STANDARDS

Complies with Canada VOC Concentration Limits for Architectural Coatings Regulations.

INSTALLATION INSTRUCTIONS

Apply by low-pressure sprayer, such as a Chapin 1949 with a 0.379 LPM nozzle, in a light, even coat. When employing a brush or roller, take care to apply as thinly and evenly as possible. A thin coating provides superior results. New wood forms (not pre-coated) should receive at least two coats before being used. All forms should be recoated before each subsequent use.

BEST USED BY

When stored indoors in original, unopened containers at temperatures between 4° - 32° C, optimum performance and best use is obtained within two years of date of manufacture.

PRECAUTIONS

For exterior use only. For industrial use only.
To be used when temperatures fall to 4° C (40° F) or colder.

WARRANTY

National Concrete Accessories warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after National Concrete Accessories has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. National Concrete Accessories shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by National Concrete Accessories. We cannot warrant or in any way guarantee any particular method of use or application of the performance of materials under and particular condition. Neither this Warranty nor our liability may be extended or amended by our sales personnel, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.

WARNING

The information contained on this package and in any promotional literature is believed to be accurate but the user assumes all risks connected with the use thereof and should conduct its own investigations and perform its own tests to determine the suitability of the product for its own particular use. Use in unsuitable circumstances can cause serious damages for which NCA is not responsible.